

Gel Tensor Material Handling

Technical data sheet

Technical features:

- Advanced maintenance-free VRLA battery (valve regulated battery technology) with gel fixed electrolyte
- Optimized tubular plate technology and negative plate design in copper expanded metal technologies for high efficiency and long cycle life
- Maintenance-free (no topping up) during the whole life due to the VRLA technology
- Extremely good charge acceptance for opportunity charge and fully charge in 8 hours
- No contamination or corrosion due to liquid electrolyte
- Very low self-discharge

Standards & certifications:

- DIN sizes according to IEC 60254-2
- Manufactured in accordance with DIN EN ISO 9001
- Environmental management in accordance with DIN EN ISO 14001



Nominal capacity:
300-1540 Ah (DIN-cells)



Single cell



Tubular plate



Recyclable



Valve regulated
lead-acid batteries



Proof against
deep discharge





Maintenance-free
(no topping up)




1250 cycles acc. to
DIN IEC 60254-1

Drawings, terminal and torque



Not to scale!



23 Nm

Gel Tensor Material Handling

Technical data sheet

Technical characteristics and data

Vented MH Essential	Gel Sonnenschein MH	Gel Tensor MH				
EPzS cell type	EPzS cell type	TCSM cell type	Height h1 ¹ [mm] Height h2 ² [mm]	Length (l) [mm]	Cell weight ³ [kg]	Nominal capacity [Ah]
3 EPzS 270	3 EPzV 240	3 TCSV 300	462 / 492	65	16,9	300
4 EPzS 360	4 EPzV 320	4 TCSV 365	462 / 492	83	21,2	365
5 EPzS 450	5 EPzV 400	5 TCSV 490	462 / 492	101	28,2	490
6 EPzS 540	6 EPzV 480	6 TCSV 545	462 / 492	119	31,9	545
7 EPzS 630	7 EPzV 560	7 TCSV 625	462 / 492	137	36,0	625
8 EPzS 720	8 EPzV 640	8 TCSV 740	462 / 492	155	42,7	740
9 EPzS 810	9 EPzV 720	9 TCSV 825	462 / 492	173	47,2	825
10 EPzS 900	10 EPzV 800	10 TCSV 940	462 / 492	191	53,4	940
3 EPzS 375	3 EPzV 300	3 TCSV 380	553 / 583	65	20,6	380
4 EPzS 500	4 EPzV 400	4 TCSV 450	553 / 583	83	26,5	450
5 EPzS 625	5 EPzV 500	5 TCSV 610	553 / 583	101	33,7	610
6 EPzS 750	6 EPzV 600	6 TCSV 690	553 / 583	119	38,6	690
7 EPzS 875	7 EPzV 700	7 TCSV 765	553 / 583	137	43,5	765
8 EPzS 1000	8 EPzV 800	8 TCSV 950	553 / 583	155	52,0	950
9 EPzS 1125	9 EPzV 900	9 TCSV 1035	553 / 583	173	56,7	1035
10 EPzS 1250	10 EPzV 1000	10 TCSV 1195	553 / 583	191	65,3	1195
3 EPzS 465	3 EPzV 360	3 TCSV 450	672 / 702	65	25,1	450
4 EPzS 620	4 EPzV 480	4 TCSV 545	672 / 702	83	31,3	545
5 EPzS 775	5 EPzV 600	5 TCSV 750	672 / 702	101	40,7	750
6 EPzS 930	6 EPzV 720	6 TCSV 870	672 / 702	119	47,1	870
7 EPzS 1085	7 EPzV 840	7 TCSV 920	672 / 702	137	51,8	920
8 EPzS 1240	8 EPzV 960	8 TCSV 1130	672 / 702	155	63,0	1130
9 EPzS 1395	9 EPzV 1080	9 TCSV 1210	672 / 702	173	70,2	1210
10 EPzS 1550	10 EPzV 1200	10 TCSV 1540	672 / 702	191	79,0	1540

¹ over cell lid

² total height incl. connector and screw

³ filled and charged (tolerance +/-5%)